



Toll Free Number. 800CEMEX
Cash Customer Hotline. 800CEMEX 4U

Dubai

Ready-Mix Concrete
CEMEX TOPMIX LLC
PO Box 37900, Al-Quoz
Industrial Area 3, Dubai, UAE
Tel : +971 4 347 0427/477 (Al-Quoz)
Fax : +971 4 347 1713
Tel : +971 4 880 1212 (Jebel Ali)
Fax : +971 4 880 1033
Email: info.dubai@cemex.com

Dubai

Cement & Slag (GGBS)
CEMEX FALCON LLC
PO Box 66429
Jebel Ali Industrial Area
Dubai, UAE
Tel : +971 4 880 1212
Fax : +971 4 880 1033

Abu Dhabi

Ready-Mix Concrete
CEMEX SUPERMIX LLC
PO Box 72071
Mussafah Industrial Area
Abu Dhabi, UAE
Tel : +971 2 551 5501
Fax : +971 2 551 5560
Email: info.abudhabi@cemex.com

www.cemex.ae
www.readymix4u.ae

Copyright © 2018 CEMEX Research Group, AG

**DURABLE
CONCRETE**

CEMEX
Building a better future

DURABLE CONCRETE



What is Durable Concrete?

CEMEX Durable concrete is a range of concrete specifically tailored to the harsh environmental conditions of the UAE. CX Durable concrete can meet the most demanding requirements for durability, through the use of environmentally friendly materials such as CEMEX Falcon Duracem GGBS.

Project Spotlight - Ferrari World, Abu Dhabi

CEMEX supplied over one hundred thousand cubic metres of a specially designed high durability concrete for the piling works of this landmark development. This concrete was designed to have very high levels of resistance to harmful chemicals present in the groundwater, whilst remaining easy to pour, pump and place.



CEMEX has over 20 years of local experience in designing concretes for the harsh climatic conditions experienced in the UAE. Our concretes can resist the harshest environmental conditions, extending the lifespan of structures.

Features and Benefits

Resistant to chemical attack

- Resistant to chloride penetration
- Resistant to sulfate attack

Low Water/Cement ratio

- Low permeability
- Dense microstructure

Extended Lifespan

- Durable concretes last longer, extending building life and enabling reuse of structures
- Reduced maintenance requirements
- Reduced lifetime cost

PERFORMANCE FOOTPRINT



TECHNICAL DATA

Concrete Grade (N/mm ²)	30 to 80
Durability ¹ (RCP, WP, WA)	800 to 3000, 10 to 20mm, 1.0 to 1.5
Workability Slump (mm)	75 to 200
Workability Retention (Hours)	up to 3
Maximum Aggregate Size (mm)	10 or 20
Typical Hardened Density (Kg/m ³)	2450
Cement Types ²	OPC, SRC, MSRPC
Supplementary Cementitious Materials ³	DURACEM®/ Microsilica
Colours	Grey or Colored

